

ACCESSORIES AND SPARE PARTS

WATER PRESSURE TANKS

SURCHARGE FOR MANHOLE AND HANDHOLE (FOR COMPRESSED AIR RECEIVERS P.E.D. 2014/68/UE)

Model	Working Pressure [bar]	Manhole (elliptical)		Handole (elliptical)		
		H5	9	H5	9	
		[mm]		[mm]		
	8	1500	860	400x300	818	150x100
		2000	890	400x300	845	150x100
		3000	985	400x300	985	150x100
		4000 (*)	1010	400x300	1010	150x100
		5000 (*)	1010	400x300	1010	150x100
		8000	//	//	1150	150x100
		10000	//	//	1150	150x100
		1000	870	400x300	840	150x100
		1500	860	400x300	818	150x100
		2000	890	400x300	845	150x100
	12	2500	985	400x300	985	150x100
		3000	985	400x300	985	150x100
		4000 (*)	1010	400x300	1010	150x100
		5000 (*)	1010	400x300	1010	150x100
		8000	//	//	1150	150x100
		10000	//	//	1150	150x100
		1000	870	400x300	840	150x100
		1500	860	400x300	818	150x100
		2000	890	400x300	845	150x100

(*) Manhole standard on 4000 - 5000 lt Polywarm® version

SURCHARGE FOR MANHOLE AND HANDHOLE (FOR AIR RECEIVERS P.E.D. 2014/68/UE)

Model	Working Pressure [bar]	Manhole (elliptical)		Handole (elliptical)		
		H6	E	H6	E	
		[mm]		[mm]		
	8	1500	860	400x300	818	150x100
		2000	890	400x300	845	150x100
		3000	985	400x300	985	150x100
		4000	1010	400x300	1010	150x100
	12	1000	870	400x300	840	150x100
		1500	860	400x300	818	150x100
		2000	890	400x300	845	150x100
		2500	985	400x300	978	150x100
		3000	985	400x300	985	150x100

AIR COMPRESSOR RECEIVERS KIT

Includes a safety valve, a gauge (manometer) and its tap-tray.



Right-side connection

Art. Nr.	Description
5303000000001	Kit for 200 up to 710 lt compressed air receivers (11 bar), with security valve of 7.000 l./min P calibration 10,4 bar
5303000000002	Kit for 900 lt compressed air receivers (11 bar), with security valve of 30.000 l./min P calibration 10,4 bar
5303000000003	Kit for 1.000 up to 10.000 lt compressed air receivers (12 bar), with security valve of 32.000 l./min P calibration 11,2 bar
5303000000004	Kit for 1.000 up to 10.000 lt compressed air receivers (8 bar), with security valve of 22.000 l./min P calibration 7,4 bar
5303000000005	Kit for 270 up to 2.000 lt compressed air receivers (15 bar), with security valve of 9.000 l./min P calibration 13,5 bar